

For 81N 8N, 8NX, 8T, 8TW4, 8WA, 8TWB

It all began in the Middle East, a land of mystery and intrigue, with Sheiks, who while riding gaily decorated camels and spirited horses, ruled the desert with golden scepters and gilded swords. This was the birthplace of the famed puzzle rings. Centuries ago these puzzle rings served as wedding bands, and were worn by women of nomadic tribes. The husband held the secrets of the rings. This guaranteed his wife's faithfulness, for the ring once removed from her fingers would fall apart.

1. Hold Band stamped 2 "1' (rounded outside band) with the irregular portion up and in your left hand. 2	2. Bring Band stamped "2" (other outside band) up against "1" band forming a diamond shape. Note - these are the outside bands when the ring is assembled.	3. Bring two more bands up on each side ("6", and "8" one side and "5" and "7" on the other). They should rest comfortably next to "'1" and "2".	4. Grasp band stamped "4" in your right hand with the stamp facing towards you, allowing remaining six bands (1,2,5,6,7,8) to fall to one side.	 5. Take the single band hanging on the bottom, stamped "3" and bring it up towards you with your left hand until the two bands are parallel. 	6. Holding the "3" band between your thumb and forefinger, tum the band clockwise.	 Continue turning until you have completed a 180-degree rotation. 	 8. The two bands should fit together locking in the 6 remaining bands. (1,2,5,6,7, and 8).
9. When you have completed the last step, if you turn the ring right side up the "3" and "4" bands should create an X.	10. Take the first band on the same side as "3"which is "8" and rotate the band until the irregular shaped part is on the inside of the ring.	 Be sure that the "v" shaped part is over the remaining loose bands. 	12. Bring band up against "3" band.	 13. Turn ring around and start rotating "7" band until the irregular shaped part is on the inside of the ring 	 14. Be sure that the "v" shaped part is over the remaining loose bands. Bring band up next to assembled bands. 	15 Turn ring around and start rotating "6" band " until the irregular shaped part is on the inside of the ring	 16. Be sure that the "v" shaped part is over the remaining loose bands. Bring band up next to assembled bands

Copyright 2011 Jose Grant Puzzle Rings - Reprinting and distribution only with the express permission of Jose Grant Puzzle Rings. For information visit www.josegrantpuzzlerings.com or e-mail Edward@josegrant.com Phone (203) 249-6737

start rotating "5" shaped band " until the the rem irregular shaped part bands.	 that the "v" part is over aining loose Bring band up assembled 19 Turn ring around and start rotating "2" band " until the irregular shaped part is on the inside of the ring. 	20. When you have completed the rotation, be sure that the "v" is over the remaining band, "1". Leave this band loose, as the tight weave requires you to complete the next steps before it will fit into place.	21. Turn ring around and start rotating "1" band (reaming band) until the irregular shaped part is on the inside of the ring. Be sure that the v shaped part is under band "2".	22. The last two bands should fall into place. If you are having problems, be sure that you have the band with the "v" part of "2" and "1" in the correct order.	23. Congratulations, you have assembled your ring.	